

CABLE-FTTH

GYFJH Optical Fiber Cable



DUST-PROOF




RoHS



WATER-PROOF



WORKING AT HEIGHTS




HIGH TEMPERATURE



WALL-HUNG TYPE



Model NO.	GYFJH
Fiber type	G657A1/G657A2
Sheath color	Black
Sheath material	LSZH
Cable dimension (mm)	4.6, Tolerance±0.1
Cable weight (Kg/km)	23
Min. bending radius (mm)	15 (Static) 10 (Dynamic)
Attenuation (dB/km)	≤ 0.4 at 1310nm ≤ 0.3 at 1550nm



- 1 Two parallel Fiber Reinforced Plastics (FRP).
- 2 PE sheath protects cable from ultraviolet radiation.



- 1 Suit for duplex connectors
- 2 LC / SC / FC / ST / MU connector



- 1 Long delivery length.
- 2 Packed by wooden drum.

SHENZHEN U1
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,
Changxing Hi-tech Industrial Park,
Shajing Street, Baoan District,
Shenzhen China 518104

CALL: +86 0755 - 2667 3886

Tel:+86 0755-2667 3886
Fax:+86 0755-2682 1069
Web: www.u1conec.com
E-mail: admin@u1conec.com