

CABLE-FTTH


JFJDH Optical Fiber Cable




Optic fiber ribbon
Aramid yarn
Outer sheath




Model NO.	GJFJDH - 4,6,8,12 B6
Fiber type	G657/G652
Sheath color	Yellow, Orange or Customized
Sheath material	LSZH or Flamed-retardant material
Cable dimension (mm)	3.2*2.5,5.0*2.5, Tolerance±0.1
Cable weight (Kg/km)	6.0-9.8
Min. bending radius (mm)	100 (Static) 50(Dynamic)
Attenuation (dB/km)	≤ 0.4 at 1310nm ≤ 0.3 at 1550nm



- 1 The flat 24core ribbon fiber are evenly bound with high tensile aramid yarn and protected by high quality outer sheath.



- 1 All-dielectric, armored, aerial self-supporting
- 2 Can be prepped and spliced much more rapidly.



- 1 Maximum fiber density relative to cable diameter.

SHENZHEN U1
TELECOMMUNICATIONS CO.,LTD

6th Floor, Building 1,
Changxing Hi-tech Industrial Park,
Shajing Street, Baoan District,
Shenzhen China 518104

CALL: +86 0755 - 2667 3886

Tel:+86 0755-2667 3886
Fax:+86 0755-2682 1069
Web: www.u1conec.com
E-mail: admin@u1conec.com